



4700 W. 160th St.
Cleveland, OH 44135
PH:800-321-9532
FX:800-321-9535
www.oatey.com

TECHNICAL SPECIFICATION

PLUMBER'S PUTTY



TECHNICAL SPECIFICATION: Oatey Plumber's Putty provides a waterproof seal between two rigid surfaces. Plumber's Putty is a stainless, long lasting, easy to use fixture setting compound for setting frames, faucets and basket strainers. Product remains flexible and resilient. Plumber's Putty will not harden, shrink, crack or crumble.



PRECAUTIONS

Read all cautions and directions carefully before using this product. **DO NOT USE PLUMBER'S PUTTY ON MARBLE, GRANITE, LIMESTONE OR ANY OTHER DIMENSIONAL STONE. DO NOT USE ON PLASTIC.** Consult manufacturer of these materials for recommended sealants. Keep container closed when not in use. **DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN AND PETS.**

Refer to material safety data sheet for more information. For emergency first aid help, call 1-303-623-5716 COLLECT.

COMMON APPLICATIONS

Oatey Plumber's Putty can be used for setting frames, faucets and basket strainers.

Consult Oatey Technical Department for applications not specifically referenced above.

NON-HAZARDOUS INGREDIENTS (CAS Number)

- Hydrocarbon Oils (64742-52-5)
- Limestone (1317-65-3)
- Talc (14807-96-6)
- Clays (68953-58-2)
- Fish Oils (68082-77-9)

APPROVALS AND LISTINGS

Meets Federal Specification TT-P-1536.

PHYSICAL/CHEMICAL PROPERTIES

Specific Gravity	2.0
Solubility in Water	Insoluble
Flash Point	650° F
Drying Time	No wait required
Shelf Life	1 year from manufacture date
Appearance	Beige Putty
Odor	Mild Petroleum Scent

DIRECTIONS FOR USE

All surfaces must be dry and free from hardened putty, dirt, wax, oil and grease. Remove debris by wiping with cloth, scraper or wire brush as needed and dry surface. Knead putty in hands and form a long cord-like shape. Lay out the cord-like putty on the surface to be sealed, overlapping the ends. Place the fixture over the bead, attach and secure the fixture in place. Excess Plumber's Putty should squeeze out from around the fixture ensuring sufficient putty has been applied and a continuous seal has been made. Remove excess with a putty knife.

PRODUCT NUMBER	SIZE	PACK	CARTON WEIGHT
31166	14 oz. Plumber's Putty	24	24 lbs.
31166D	14 oz. Plumber's Putty – Display	30	31 lbs.
311660	14 oz. Plumber's Putty – Mini-pallet	270	275 lbs.
31170	3 lbs. Plumber's Putty	6	20 lbs.
31174	5 lbs. Plumber's Putty	6	32 lbs.
31174D	5 lbs. Plumber's Putty – Display	6	32 lbs.