

1301 E. 9th Street, #700
Cleveland OH 44114
(800) 726-9626



Material Safety Data Sheet

MSDS Form No. : 039451
Item No. : BD1494, BD1494-1
MATERIAL SAFETY DATA SHEET

BD1494
01 00

DATE OF PREPARATION: NOV 14, 2012

-----SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION -----

PRODUCT NUMBER: BD1494

PRODUCT NAME: PREMIUM GLASS CLEANER

MANUFACTURER'S NAME:
MFG. FOR: BARNES DISTRIBUTION
1301 EAST 9TH ST., SUITE 700
CLEVELAND, OH 44114-1824

TELEPHONE NUMBERS AND WEBSITES:

PRODUCT INFORMATION:
(866) GET-MROP
WWW.BARNESDISTRIBUTION.COM

REGULATORY INFORMATION: (216) 566-2902

MEDICAL EMERGENCY: (303) 623-5716

TRANSPORTATION EMERGENCY*: (800) 424-9300

*FOR CHEMICAL EMERGENCY ONLY (SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT)

-----SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS -----

% BY WEIGHT	CAS NUMBER	INGREDIENT	UNITS	VAPOR PRESSURE
1	74-98-6	PROPANE ACGIH TLV: 2500 PPM OSHA PEL: 1000 PPM		760 MM
3	106-97-8	BUTANE ACGIH TLV: 800 PPM -----		760 MM

OSHA PEL: 800 PPM

1	64-17-5	ETHANOL ACGIH TLV: 1000 PPM OSHA PEL: 1000 PPM	44 MM
2	111-76-2	2-BUTOXYETHANOL ACGIH TLV: 20 PPM OSHA PEL: 25 PPM	0.88 MM
1	110-91-8	MORPHOLINE ACGIH TLV: 20 PPM (SKIN) ACGIH TLV: 30 PPM (SKIN) STEL OSHA PEL: 20 PPM (SKIN) OSHA PEL: 30 PPM (SKIN) STEL	7 MM

-----SECTION 3 - HAZARDS IDENTIFICATION -----

HMIS CODES:
HEALTH 3
FLAMMABILITY 2
REACTIVITY 0

ROUTES OF EXPOSURE:
INHALATION OF VAPOR OR SPRAY MIST.
EYE OR SKIN CONTACT WITH THE PRODUCT, VAPOR OR SPRAY MIST.

EFFECTS OF OVEREXPOSURE:

EYES: IRRITATION.

SKIN: PROLONGED OR REPEATED EXPOSURE MAY CAUSE IRRITATION.

INHALATION:

IRRITATION OF THE UPPER RESPIRATORY SYSTEM.

MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE MAY RESULT IN
UNCONSCIOUSNESS AND POSSIBLY DEATH.

PROLONGED OVEREXPOSURE TO HAZARDOUS INGREDIENTS IN SECTION 2 MAY CAUSE ADVERSE
CHRONIC EFFECTS TO THE FOLLOWING ORGANS OR SYSTEMS:

THE LIVER
THE URINARY SYSTEM
THE HEMATOPOIETIC (BLOOD-FORMING) SYSTEM

SIGNS AND SYMPTOMS OF OVEREXPOSURE:
HEADACHE, DIZZINESS, NAUSEA, AND LOSS OF COORDINATION ARE INDICATIONS OF
EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS. REDNESS AND ITCHING OR BURNING
SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN EXPOSURE.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NONE GENERALLY RECOGNIZED.

CANCER INFORMATION:
FOR COMPLETE DISCUSSION OF TOXICOLOGY DATA REFER TO SECTION 11.

-----SECTION 4 - FIRST AID MEASURES -----

EYES:
FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

SKIN:
WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER.
REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE RE-USE.

INHALATION:
IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET.

INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

-----SECTION 5 - FIRE FIGHTING MEASURES -----

FLASH POINT: PROPELLANT <0 DEG. F

LEL: 1.1
UEL: 19.0

EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS:

CLOSED CONTAINERS MAY EXPLODE (DUE TO THE BUILD-UP OF PRESSURE) WHEN EXPOSED TO EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.

DURING EMERGENCY CONDITIONS OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.

SPECIAL FIRE FIGHTING PROCEDURES:

FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED.

WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

-----SECTION 6 - ACCIDENTAL RELEASE MEASURES -----

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
REMOVE ALL SOURCES OF IGNITION. VENTILATE THE AREA.
REMOVE WITH INERT ABSORBENT.

-----SECTION 7 - HANDLING AND STORAGE -----

STORAGE CATEGORY: NOT AVAILABLE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. VAPORS WILL ACCUMULATE READILY AND MAY IGNITE EXPLOSIVELY.

DURING USE AND UNTIL ALL VAPORS ARE GONE:
KEEP AREA VENTILATED - DO NOT SMOKE - EXTINGUISH ALL FLAMES, PILOT LIGHTS, AND HEATERS - TURN OFF STOVES, ELECTRIC TOOLS AND APPLIANCES, AND ANY OTHER SOURCES OF IGNITION.

CONSULT NFPA CODE. USE APPROVED BONDING AND GROUNDING PROCEDURES.

CONTENTS UNDER PRESSURE. DO NOT PUNCTURE, INCINERATE, OR EXPOSE TO TEMPERATURE ABOVE 120F. HEAT FROM SUNLIGHT, RADIATORS, STOVES, HOT WATER, AND OTHER HEAT SOURCES COULD CAUSE CONTAINER TO BURST. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

-----SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION -----

PRECAUTIONS TO BE TAKEN IN USE:
USE ONLY WITH ADEQUATE VENTILATION.
AVOID CONTACT WITH SKIN AND EYES. AVOID BREATHING VAPOR AND SPRAY MIST.
WASH HANDS AFTER USING.

VENTILATION:

LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE EXPOSURE TO MATERIALS IN SECTION 2 IS MAINTAINED BELOW APPLICABLE EXPOSURE LIMITS. REFER TO OSHA STANDARDS 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION:

IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA FOR PROTECTION AGAINST MATERIALS IN SECTION 2.

PROTECTIVE GLOVES:

NONE REQUIRED FOR NORMAL APPLICATION OF AEROSOL PRODUCTS WHERE MINIMAL SKIN CONTACT IS EXPECTED. FOR LONG OR REPEATED CONTACT, WEAR CHEMICAL RESISTANT GLOVES.

EYE PROTECTION: WEAR SAFETY SPECTACLES WITH UNPERFORATED SIDESHIELDS.

OTHER PRECAUTIONS:

INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

-----SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES -----

PRODUCT WEIGHT:

8.02 LB/GAL
960 G/L

SPECIFIC GRAVITY: 0.96

BOILING POINT:

<0 - 343 DEG. F
<-18 - 172 DEG. C

MELTING POINT: NOT AVAILABLE

VOLATILE VOLUME: 99%

EVAPORATION RATE: FASTER THAN ETHER

VAPOR DENSITY: HEAVIER THAN AIR

SOLUBILITY IN WATER: NOT AVAILABLE

PH: 10.0

VOLATILE ORGANIC COMPOUNDS (VOC THEORETICAL - AS PACKAGED):

VOLATILE WEIGHT 8.05% LESS WATER AND FEDERALLY EXEMPT SOLVENTS

-----SECTION 10 - STABILITY AND REACTIVITY -----

STABILITY: STABLE

CONDITIONS TO AVOID: NONE KNOWN.

INCOMPATIBILITY: NONE KNOWN.

HAZARDOUS DECOMPOSITION PRODUCTS:

BY FIRE: CARBON DIOXIDE, CARBON MONOXIDE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

-----SECTION 11 - TOXICOLOGICAL INFORMATION -----

CHRONIC HEALTH HAZARDS:

NO INGREDIENT IN THIS PRODUCT IS AN IARC, NTP OR OSHA LISTED CARCINOGEN.

REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

TOXICOLOGY DATA:

CAS NO.	INGREDIENT NAME
74-98-6	PROPANE LC50 RAT 4HR: NOT AVAILABLE LD50 RAT: NOT AVAILABLE
106-97-8	BUTANE LC50 RAT 4HR: NOT AVAILABLE LD50 RAT: NOT AVAILABLE
64-17-5	ETHANOL LC50 RAT 4HR: NOT AVAILABLE LD50 RAT: 7060 MG/KG
111-76-2	2-BUTOXYETHANOL LC50 RAT 4HR: NOT AVAILABLE LD50 RAT: 470 MG/KG
110-91-8	MORPHOLINE LC50 RAT 4HR: NOT AVAILABLE LD50 RAT: 1050 MG/KG

-----SECTION 12 - ECOLOGICAL INFORMATION -----

ECOTOXICOLOGICAL INFORMATION: NO DATA AVAILABLE.

-----SECTION 13 - DISPOSAL CONSIDERATIONS -----

WASTE DISPOSAL METHOD:

WASTE FROM THIS PRODUCT MAY BE HAZARDOUS AS DEFINED UNDER THE RESOURCE CONSERVATION AND RECOVERY ACT (RCRA) 40 CFR 261.

WASTE MUST BE TESTED FOR IGNITABILITY TO DETERMINE THE APPLICABLE EPA HAZARDOUS WASTE NUMBERS.

DO NOT INCINERATE. DEPRESSURIZE CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE/PROVINCIAL, AND LOCAL REGULATIONS REGARDING POLLUTION.

-----SECTION 14 - TRANSPORT INFORMATION -----

MULTI-MODAL SHIPPING DESCRIPTIONS ARE PROVIDED FOR INFORMATIONAL PURPOSES AND DO NOT CONSIDER CONTAINER SIZES. THE PRESENCE OF A SHIPPING DESCRIPTION FOR A PARTICULAR MODE OF TRANSPORT (OCEAN, AIR, ETC.), DOES NOT INDICATE THAT THE PRODUCT IS PACKAGED SUITABLY FOR THAT MODE OF TRANSPORT. ALL PACKAGING MUST BE REVIEWED FOR SUITABILITY PRIOR TO SHIPMENT, AND COMPLIANCE WITH THE APPLICABLE REGULATIONS IS THE SOLE RESPONSIBILITY OF THE PERSON OFFERING THE PRODUCT FOR TRANSPORT.

US GROUND (DOT):

MAY BE CLASSED AS LTD. QTY. OR ORM-D
UN1950, AEROSOLS, 2.2, LIMITED QUANTITY, (ERG#126)

CANADA (TDG):

MAY BE CLASSED AS LTD. QTY. OR ORM-D
UN1950, AEROSOLS, CLASS 2.2, LIMITED QUANTITY, (ERG#126)

IMO:

MAY BE SHIPPED AS LIMITED QUANTITY
UN1950, AEROSOLS, CLASS 2.1, LIMITED QUANTITY, EMS F-D, S-U, ADR (D)

IATA/ICAO: UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, LIMITED QUANTITY

-----SECTION 15 - REGULATORY INFORMATION -----

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION:

CAS NO.	CHEMICAL/COMPOUND	% BY WT	% ELEMENT
	GLYCOL ETHERS	2	

CALIFORNIA PROPOSITION 65:

WARNING:

THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

TSCA CERTIFICATION:

ALL CHEMICALS IN THIS PRODUCT ARE LISTED, OR ARE EXEMPT FROM LISTING, ON THE TSCA INVENTORY.

-----SECTION 16 - OTHER INFORMATION -----

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CANADIAN CONTROLLED PRODUCTS REGULATIONS (CPR) AND THE MSDS CONTAINS ALL OF THE INFORMATION REQUIRED BY THE CPR.

THE ABOVE INFORMATION PERTAINS TO THIS PRODUCT AS CURRENTLY FORMULATED, AND IS BASED ON THE INFORMATION AVAILABLE AT THIS TIME. ADDITION OF REDUCERS OR OTHER ADDITIVES TO THIS PRODUCT MAY SUBSTANTIALLY ALTER THE COMPOSITION AND HAZARDS OF THE PRODUCT. SINCE CONDITIONS OF USE ARE OUTSIDE OUR CONTROL, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THIS INFORMATION.