		Page: 1
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 3/23/2016
		SDS Number: R0177148
Pyroil™ DEICER		Version: 1.1
PYDI11.5		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Pyroil™
DEICER

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet Niteo Products, LLC P.O. Box 191629 Dallas TX 75219 United States of America	Emergency telephone number CHEMTREC DIRECT 1-800-424-9300 Product Information 1-844-696-4836
--	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable aerosols : Category 2

Acute toxicity (Oral) : Category 3

Acute toxicity (Inhalation) : Category 3

Acute toxicity (Dermal) : Category 3

Specific target organ systemic toxicity - single exposure : Category 1 (Central nervous system, Eyes)

Specific target organ systemic toxicity - repeated exposure (Oral) : Category 2 (Kidney, Liver)

GHS Label element

Hazard pictograms :   

Signal Word : Danger

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 3/23/2016

SDS Number: R0177148

Pyroil™ DEICER

Version: 1.1

PYDI11.5

Hazard Statements : Flammable aerosol.
 Toxic if swallowed, in contact with skin or if inhaled.
 Causes damage to organs (Central nervous system, Eyes).
 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Precautionary Statements : **Prevention:**
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
 Wash skin thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/ protective clothing.
Response:
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Rinse mouth.
 IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or doctor/ physician if you feel unwell.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician.
 IF exposed: Call a POISON CENTER or doctor/ physician.
 Take off contaminated clothing and wash before reuse.
Storage:
 Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Disposal:
 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
METHANOL	67-56-1	Flam. Liq. 2; H225 Acute Tox. 3; H301	62.45

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 3/23/2016

SDS Number: R0177148

Pyroil™ DEICER


Version: 1.1

PYDI11.5

		Acute Tox. 3; H331 Acute Tox. 3; H311 STOT SE 1; H370	
ETHYLENE GLYCOL	107-21-1	Acute Tox. 4; H302 STOT RE 2; H373	5.92
CARBON DIOXIDE	124-38-9	Press. Gas Liquefied gas; H280	1.76

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
Call a physician or poison control centre immediately.
Keep patient warm and at rest.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
Wash contaminated clothing before re-use.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Get medical attention immediately.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

		Page: 4
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 3/23/2016
		SDS Number: R0177148
Pyroil™ DEICER		Version: 1.1
PYDI11.5		

Most important symptoms and effects, both acute and delayed

: This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis.

Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnea, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 post-exposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

- stomach or intestinal upset (nausea, vomiting, diarrhea)
- irritation (nose, throat, airways)
- Cough
- muscle cramps
- pain in the abdomen and lower back
- Blurred vision
- Shortness of breath
- cyanosis (causes blue coloring of the skin and nails from lack of oxygen)
- lung edema (fluid buildup in the lung tissue)
- acute kidney failure (sudden slowing or stopping of urine production)
- visual impairment (including blindness)
- Convulsions
- Toxic if swallowed, in contact with skin or if inhaled
- Causes damage to organs.
- May cause damage to organs through prolonged or repeated exposure if swallowed.

Notes to physician

: This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 3/23/2016

SDS Number: R0177148

Pyroil™ DEICER

Version: 1.1


PYDI11.5

severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Alcohol-resistant foam
Carbon dioxide (CO2)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Alcohols
Aldehydes
ethers
toxic fumes
- Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

		Page: 6
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 3/23/2016
		SDS Number: R0177148
Pyroil™ DEICER		Version: 1.1
PYDI11.5		

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ensure adequate ventilation.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Other information : Comply with all applicable federal, state, and local regulations.
Suppress (knock down) gases/vapours/mists with a water spray jet.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Open drum carefully as content may be under pressure.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Take precautionary measures against static discharges.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
Container may be opened only under exhaust ventilation hood.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.
Electrical installations / working materials must comply with the technological safety standards.

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 3/23/2016

SDS Number: R0177148

Pyroil™ DEICER

Version: 1.1

PYDI11.5

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
METHANOL	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		REL	200 ppm 260 mg/m ³	NIOSH/GUID E
		STEL	250 ppm 325 mg/m ³	NIOSH/GUID E
		PEL	200 ppm 260 mg/m ³	OSHA_TRANS
		TWA	200 ppm 260 mg/m ³	TN OEL
		STEL	250 ppm 325 mg/m ³	TN OEL
ETHYLENE GLYCOL	107-21-1	Ceiling	100 mg/m ³ Aerosol.	ACGIH
		TWA	10 mg/m ³ Inhalable fraction and vapor	ACGIHLIS_P
CARBON DIOXIDE	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		REL	5,000 ppm 9,000 mg/m ³	NIOSH/GUID E
		STEL	30,000 ppm 54,000 mg/m ³	NIOSH/GUID E
		PEL	5,000 ppm 9,000 mg/m ³	OSHA_TRANS

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
METHANOL	67-56-1	methanol	Urine	Sampling time: End of shift.	15 mg/l	
Remarks:	Background, Nonspecific					

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 3/23/2016

SDS Number: R0177148

Pyroil™ DEICER

Version: 1.1

PYDI11.5

otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

- Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:
impervious clothing
Safety shoes
Flame-resistant clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : aerosol
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : 148.5 °F / 64.7 °C
(1,013.25 hPa)
Value for Component
- Flash point : 54 °F / 12 °C
Calculated Flash Point
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : 36 %(V)
GLP: Calculated Explosive Limit

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 3/23/2016

SDS Number: R0177148

Pyroil™ DEICER

Version: 1.1

PYDI11.5

Lower explosion limit	: 3.2 %(V) GLP: Calculated Explosive Limit
Vapour pressure	: 169.3164 hPa (25 °C) Value for Component
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.7972 g/cm3 (15.56 °C)
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Oxidizing properties	: No data available
Heat of combustion	: Estimated 15.35 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. excessive heat
Incompatible materials	: Aldehydes Alkali metals Alkaline earth metals aluminum Lead

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 3/23/2016

SDS Number: R0177148

Pyroil™ DEICER

Version: 1.1

PYDI11.5

sodium
 Strong acids
 strong bases
 Strong oxidizing agents
 Sulphur compounds
 Zinc
 Peroxides

Hazardous decomposition products

Aldehydes
 carbon dioxide and carbon monoxide
 formaldehyde-like
 Organic acids
 ketones

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
 Skin contact
 Eye Contact
 Ingestion

Acute toxicity

Toxic if swallowed, in contact with skin or if inhaled

Components:
METHANOL:

Acute oral toxicity : LD L0 (Human): 300 mg/kg
 Assessment: The component/mixture is classified as acute oral toxicity, category 3.

Acute inhalation toxicity : LC 50 (Rat): 64000 ppm
 Exposure time: 4 h
 Assessment: The component/mixture is classified as acute inhalation toxicity, category 3.
 Remarks: Slightly toxic by inhalation

Acute dermal toxicity : LD 50 (Rabbit): 12,800 mg/kg
 Assessment: The component/mixture is classified as acute dermal toxicity, category 3.

ETHYLENE GLYCOL:

Acute oral toxicity : LD 50 (Rat): 6,140 mg/kg
 LD50 (Human): Estimated 1.56 g/kg
 Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Acute inhalation toxicity : LC 50 (Rat): 10.9 mg/l
 Exposure time: 1 h
 Test atmosphere: dust/mist

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 3/23/2016

SDS Number: R0177148

Pyroil™ DEICER

Version: 1.1

PYDI11.5

Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit): 9,530 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Components:**METHANOL:**

Species: Rabbit

Result: Not irritating to skin

ETHYLENE GLYCOL:

Result: Mildly irritating to skin

CARBON DIOXIDE:

Result: Not irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:**METHANOL:**

Species: Rabbit

Result: Mildly irritating to eyes

ETHYLENE GLYCOL:

Result: Possibly irritating to eyes

CARBON DIOXIDE:

Result: Not irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:**METHANOL:**

Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Assessment: Does not cause skin sensitisation.


Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

		Page: 12
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 3/23/2016
		SDS Number: R0177148
Pyroil™ DEICER		Version: 1.1
PYDI11.5		

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Causes damage to organs (Central nervous system, Eyes).

Components:

METHANOL:

Target Organs: Central nervous system, Eyes

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

STOT - repeated exposure

May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Components:

ETHYLENE GLYCOL:

Exposure routes: Ingestion

Target Organs: Kidney, Liver

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

Components:

METHANOL:

Remarks: Central nervous system

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

METHANOL:

Toxicity to fish : LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss)): 18,000 - 20,000 mg/l

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 3/23/2016

SDS Number: R0177148

Pyroil™ DEICER

Version: 1.1

PYDI11.5

Exposure time: 96 h

Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): > 10,000 mg/l
 Exposure time: 48 h
 Test Type: static test

ETHYLENE GLYCOL:

Toxicity to fish : LC 50 (Bluegill (Lepomis macrochirus)): 27,540 mg/l
 Exposure time: 96 h
 Method: Static
 Remarks: Mortality

LC 50 (Fathead minnow (Pimephales promelas)): 8,050 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC 50 (Water flea (Daphnia magna)): > 10,000 mg/l
 Exposure time: 48 h
 Test Type: static test

Persistence and degradability

Components:

METHANOL:

Biodegradability : Biodegradation: 99 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301D

Bioaccumulative potential

Components:

METHANOL:

Partition coefficient: n-octanol/water : log Pow: -0.77

ETHYLENE GLYCOL:

Bioaccumulation : Species: Crayfish (Procambarus)
 Bioconcentration factor (BCF): 0.27
 Exposure time: 61 d
 Concentration: 1000 mg/l
 Method: Flow through

Partition coefficient: n-octanol/water : log Pow: -1.36

Mobility in soil

Components:

No data available

Other adverse effects

No data available

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 3/23/2016

SDS Number: R0177148

Pyroil™ DEICER

Version: 1.1

PYDI11.5

Product:

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., May cause long lasting harmful effects to aquatic life.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice

: The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging

: Empty remaining contents.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN	1950	Aerosols	2		LIMITED QUANTITY
----	------	----------	---	--	------------------

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN	1950	Aerosols	2.1		LIMITED QUANTITY
----	------	----------	-----	--	------------------

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN	1950	Aerosols	2.1		LIMITED QUANTITY
----	------	----------	-----	--	------------------

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 3/23/2016

SDS Number: R0177148

Pyroil™ DEICER

Version: 1.1

PYDI11.5

INTERNATIONAL MARITIME DANGEROUS GOODS

UN	1950	AEROSOLS	2.1	LIMITED QUANTITY
----	------	----------	-----	------------------

TRANSPORT CANADA - INLAND WATERWAYS

UN	1950	AEROSOLS	2.1	LIMITED QUANTITY
----	------	----------	-----	------------------

TRANSPORT CANADA - RAIL

UN	1950	AEROSOLS	2.1	LIMITED QUANTITY
----	------	----------	-----	------------------

TRANSPORT CANADA - ROAD

UN	1950	AEROSOLS	2.1	
----	------	----------	-----	--

U.S. DOT - INLAND WATERWAYS

UN	1950	Aerosols, flammable	2.1	
----	------	---------------------	-----	--

U.S. DOT - RAIL

UN	1950	Aerosols, flammable	2.1	
----	------	---------------------	-----	--

U.S. DOT - ROAD

UN	1950	AEROSOLS	2.1	
----	------	----------	-----	--

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
METHANOL	67-56-1	5000	8005.379615

SARA 311/312 Hazards : Acute Health Hazard

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 3/23/2016

SDS Number: R0177148

Pyroil™ DEICER

Version: 1.1

PYDI11.5

Fire Hazard
Chronic Health Hazard

SARA 313 Component(s)

METHANOL	67-56-1	62.45 %
ETHYLENE GLYCOL	107-21-1	5.92 %

Pennsylvania Right To Know

METHANOL	67-56-1	50.00 - 70.00 %
WATER	7732-18-5	20.00 - 30.00 %
ETHYLENE GLYCOL	107-21-1	5.00 - 10.00 %
CARBON DIOXIDE	124-38-9	1.00 - 5.00 %

New Jersey Right To Know

METHANOL	67-56-1	50.00 - 70.00 %
WATER	7732-18-5	20.00 - 30.00 %
ETHYLENE GLYCOL	107-21-1	5.00 - 10.00 %
CARBON DIOXIDE	124-38-9	1.00 - 5.00 %

California Prop 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

METHANOL	67-56-1
ETHYLENE GLYCOL MONOMETHYL ETHER	109-86-4

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL.
- AICS : On the inventory, or in compliance with the inventory
- NZIOC : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

Inventories

NiTEO PRODUCTS		Page: 17
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 3/23/2016
		SDS Number: R0177148
Pyroil™ DEICER		Version: 1.1
PYDI11.5		

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2015

NFPA:	HMIS III:						
<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr> <td>HEALTH</td> <td>2*</td> </tr> <tr> <td>FLAMMABILITY</td> <td>3</td> </tr> <tr> <td>PHYSICAL HAZARD</td> <td>0</td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2*	FLAMMABILITY	3	PHYSICAL HAZARD	0
HEALTH	2*						
FLAMMABILITY	3						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Not applicable

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.


Sources of key data used to compile the Safety Data Sheet

Internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Cefic, the European Chemical Industry Council.

ESIS European Chemical Substances Information System

		Page: 18
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 3/23/2016
		SDS Number: R0177148
Pyroil™ DEICER		Version: 1.1
PYDI11.5		

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System